





One kit for all

Transcend's 2.5" SSD/HDD Enclosure Kit includes a 2.5-inch enclosure with an outer rubber case, an inner rubber shock absorber, a SATA adapter, a USB cable, a 7mm to 9.5mm spacer, a PH1 screwdriver, and three M2 mounting screws.



Shock absorbing rubber for rugged protection

Included in the kit is an outer rubber case and an inner rubber shock absorber for optimum protection against shock and vibration. If your original hard drive is only 7mm in height, a spacer is included to increase the thickness by 2.5mm, allowing your drive to perfectly fit inside the inner rubber shock absorber.



One touch for easy backup

Transcend's 2.5" SSD/HDD Enclosure Kit features a one-touch backup function enabling the express synchronization of files and folders by just one touch. Download the Transcend Elite software from our website to manage your data in a more organized way!

Note: Transcend 2.5" SATA III SSD and Elite software is required for this feature.

Learn more





Accessories 2.5" SSD/HDD Enclosure Kit

Features

- USB 3.1 Gen 1 interface
- SATA III 6Gb/s adapter interface
- A 7mm to 9.5mm spacer is included
- Supports Transcend Elite software for data management and SSD Scope for system clone



SSD Scope

SSD Scope features useful functions to maintain your SSD in a healthy status and also copy data from your original HDD to Transcend's new SSD.





Transcend Elite

Transcend Elite is a data management software for external hard drives, USB flash drives and portable SSD products.

Specifications

Appearance

Dimensions	129.5 mm x 80.8 mm x 18.8 mm (5.10" x 3.18" x 0.74")
Weight	108 g (3.8 oz)
Interface	
Connection Interface	USB 3.1 Gen 1
Bus Interface	SATA III 6Gb/s
Operating Environment	
Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V
Warranty	
Certificate	CE / FCC / BSMI / KC / RCM / UKCA
Warranty	Two-year Limited Warranty
Package	
Package Contents	Enclosure / USB cable / 7mm to 9.5mm spacer / PH1 screwdriver

Ordering Information

0MB TS0GSJ25CK3

/ M2 mounting screws

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.