





Exmor™ high-sensitivity image sensor

The DrivePro 230 uses an Exmor™ sensor to capture high-resolution images with superb, rich color even in low light. Its built-in Wide Dynamic Range (WDR) technology balances the light and dark areas of captured images, ensuring that every critical shot is as clear as possible.



GPS/GLONASS receiver

The DrivePro 230's GPS/GLONASS receiver can log coordinates, date, and time into recorded video footage. The coordinates precisely locate where an incident happened so that emergency road services, police, or an insurance representative can respond more quickly.



Handy snapshot function

The snapshot button allows you to take photos while still recording video.
During an incident, you can remove the DrivePro 230 from the vehicle to create a photographic record of collision damage.





Dashcams

DrivePro™ 230

Features

- · Exmor™ high-sensitivity image sensor
- Built-in GPS/GLONASS receiver logs your driving path
- Built-in Wi-Fi function for mobile live streaming
- Built-in battery prevents losing crucial images in the event of a power outage
- Parking mode and time-lapse video safeguard your vehicle continuously



DrivePro Toolbox Software

The DrivePro Toolbox is developed for Transcend DrivePro series. Featured a user-friendly interface, the DrivePro Toolbox allows you to select and play videos recorded on your DrivePro Car Video Recorder without the need to install separate codecs.

Specification

| Α | n | n | \triangle | = | r | = | n | \sim | \mathcal{L} |
|---------------|---|---|-------------|---|---|---|---|--------|---------------|
| $\overline{}$ | U | U | | u | | u | | • | · |

| Dimensions | 70.2 mm x 63.1 mm x 34.5 mm (2.76" x 2.48" x 1.36") |
|------------------------|---|
| Weight | 81 g (2.86 oz) |
| Interface | |
| USB Type | micro USB to car lighter adapter |
| Connection Interface | USB 2.0 |
| Network Interface | Wi-Fi 802.11n |
| Hardware | |
| Display | 2.4" color TFT LCD |
| Viewing Angle for Lens | 130° (diagonal) |
| | |

F/2.0

Operating Environment

Aperture

Resolution

Certificate

Warranty

| Format | |
|-----------------------|------------------------------|
| Output Voltage | 5V / 1A |
| Input Voltage | 12V ~ 24V |
| Storage Temperature | -25°C (-13°F) ~ 70°C (158°F) |
| Operating Temperature | -20°C (-4°F) ~ 65°C (149°F) |

| Frame Rate | 30 fps | |
|--------------|-------------|--|
| Video Format | MOV (H.264) | |
| Warranty | | |

CE/FCC/BSMI/NCC/MIC/KC/EAC
Two-year Limited Warranty

Full HD 1080P

Ordering Information

| 32GB | TS-DP230M-32G (Suction Mount) |
|------|-------------------------------|
| | |

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.